



PANEL CUT OUT

TECHNICAL SPECIFICATION :

PARAMETERS	SERIES	E-FH1
Mounting style		Panel
Permissible Temp.with/Without load		-20°C to +85°C
Permissible Temp. for Soldering		270° for 5 seconds max.
Panel Thickness(Max.)		6mm max.
Material: Polyamide		Polyamide. G.F
Insulation Resistance		1000 M Ohms min.
H.V. Break Down		2KV/AC For 1 Minute
Current Carrying Parts		Brss,Tin Plated
contact Resistance(Initial)		10 m Ohms max.
Cap Design		Screw-In
App.Weight(gm)		6.0
Fuse Link Size		5x20 mm
Rated Current/Voltage		6.3 Amps/250V AC
Terminals		Solder type

NOTE:-ALL DIMENSION IN MM

TITLE:- FUSE HOLDER (E-FH1)

S.NO.	PROD DWG DESCRIPTION	SIZE	QTY	MATERIAL	REMARKS
	SCALE 1:1	DATE			5/09/13
		DRAWN			AJV
		CHECKED			
		APPROVED			
	MATERIAL				
	DRG.NO.				

NANOLETRIC CONTROLS
 Gat No.245,246,247,249/1,3b.
 Kharabwadi, Chakan-410501